

**INTERTANKO CHARTERING QUESTIONNAIRE 88 - OIL/CHEMICAL**
**Version 5**

<b>1.</b>	<b>GENERAL INFORMATION</b>		
1.1	Date updated:	01/03/2022	
1.2	Vessel's name (IMO number):	Zakros (9352872)	
1.3	Vessel's previous name(s) and date(s) of change:	Lukianos / 28.01.2020	
1.4	Date delivered/Builder (where built):	Oct 25, 2005/Nakatani Shipyard, Hiroshima, Japan	
1.5	Flag/Port of Registry:	Greek / Piraeus	
1.6	Call sign/MMSI:	SVDG9/241699000	
1.7	Vessel's contact details (satcom/fax/email etc.):	Email: tankerzakros@sekavin.gr	
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC):	Oil Tanker	
1.9	Type of hull:	Double Hull	
<b>Ownership and Operation</b>			
1.10	Registered owner - Full style:	ZAKROS SHIPPING COMPANY 53-55, Akti Miaouli 185 36 Piraeus – Greece PHONE : 210 4293160 FAX : 210 4295068	
1.11	Technical operator - Full style:	ZAKROS SHIPPING COMPANY 53-55, Akti Miaouli 185 36 Piraeus – Greece PHONE : 210 4293160 FAX : 210 4295068	
1.12	Commercial operator - Full style:	SEKAVIN REPLENISHMENT STATIONS FOR TRANSPORTATION MEANS TOURIST ENTERPRISES SA (SEKAVIN SA) 53-55, Akti Miaouli 185 36 Piraeus – Greece PHONE : 210 4293160 FAX : 210 4295068 Site : www.sekavin.com	
1.13	Disponent owner - Full style:	N/A	
<b>Insurance</b>			
1.14	P & I Club - Full Style:	Shipowners mutual protection & indemnity association	
1.15	P & I Club pollution liability coverage/expiration date:	1,000,000,000 US\$	04/02/2023
1.16	Hull & Machinery insured by - Full Style: (Specify broker or leading underwriter)	Sea Scope Insurance Services Ltd. 57 Mansell Street, London E1 8AN Tel: 02074883288, Fax: 02074814499	
1.17	Hull & Machinery insured value/expiration date:	4,400,000 USD + INCREASED VALUE 1,100,000 USD	11/04/2022
<b>Classification</b>			
1.18	Classification society:	RINA	
1.19	Class notation:	Oil tanker ESP – Double Hull – unrestricted navigation, AUT-UMS	
1.20	Is the vessel subject to any conditions of class, class extensions, outstanding memorandums or class recommendations? If yes, give details:	No NA	
1.21	If classification society changed, name of previous and date of change:	NKK, 08/05/2020	
1.22	Does the vessel have ice class? If yes, state what level:	No, NA	
1.23	Date/place of last dry-dock:	June 25, 2020 Greece Perama	
1.24	Date next dry dock due/next annual survey due:	June 25, 2023	Jan 24, 2022
1.25	Date of last special survey/next special survey due:	Oct 01, 2020	Oct 24, 2025
1.26	If ship has Condition Assessment Program (CAP), what is the latest overall rating:	No,	
<b>Dimensions</b>			
1.27	Length overall (LOA):	90.04 Metres	
1.28	Length between perpendiculars (LBP):	84.00 Metres	

1.29	Extreme breadth (Beam):			14.70 Metres	
1.30	Moulded depth:			6.80 Metres	
1.31	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:		31.74 Metres	31.74 Metres	
1.32	Distance bridge front to center of manifold:			30.55 Metres	
1.33	Bow to center manifold (BCM)/Stern to center manifold (SCM):		39.10 Metres	50.90 Metres	
1.34	Parallel body distances	Lightship	Normal Ballast	Summer Dwt	
	Forward to mid-point manifold:	8.75 Metres	12.60 Metres	14.33 Metres	
	Aft to mid-point manifold:	19.53 Metres	25.35 Metres	28.50 Metres	
	Parallel body length:	28.28 Metres	37.95 Metres	42.83 Metres	
<b>Tonnages</b>					
1.35	Net Tonnage:			1,099.00	
1.36	Gross Tonnage/Reduced Gross Tonnage (if applicable):		2,547.00		
1.37	Suez Canal Tonnage - Gross (SCGT)/Net (SCNT):		2,730.30	2,079.04	
1.38	Panama Canal Net Tonnage (PCNT):			2,193.30	
<b>Loadline Information</b>					
1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	1.51 Metres	5.31 Metres	3,644.83 Metric Tonnes	5,157.17 Metric Tonnes
	Winter:	1.62 Metres	5.20 Metres	3,524.37 Metric Tonnes	5,036.71 Metric Tonnes
	Tropical:	1.40 Metres	5.42 Metres	3,765.95 Metric Tonnes	5,278.29 Metric Tonnes
	Lightship:	4.83 Metres	1.97 Metres	-	1,512.34 Metric Tonnes
	Normal Ballast Condition:	2.91 Metres	3.89 Metres	2,126.83 Metric Tonnes	3,639.17 Metric Tonnes
	Segregated Ballast Condition:	2.91 Metres	3.89 Metres	2,126.83 Metric Tonnes	3,639.17 Metric Tonnes
1.40	FWA/TPC at summer draft:			117.00 Millimetres	10.97 Metric Tonnes
1.41	Does vessel have multiple SDWT? If yes, please provide all assigned loadlines:	No Loadline Cert no. 1 (In used): Summer Draft - 5.313 M Freeboard - 1.509 M DWT - 3644.83 T			
1.42	Constant (excluding fresh water):				
1.43	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?	Deep Sea Passage depth >100m (5 x the deepest draft). Coastal Pass depth >50m (twice the depth of Draft). Approach to Port <50m/OPL 15% of deep draft. Within Port Limit: while underway at SPM Buoys + Anchorage - 10% of deepest Draft. Berth in Ports - 60cm UKC.			
1.44	What is the max height of mast above waterline (air draft)		Full Mast	Collapsed Mast	
	Summer deadweight:		26.43 Metres	0 Metres	
	Normal ballast:		27.85 Metres	0 Metres	
	Lightship:		29.77 Metres	0 Metres	

<b>2.</b>	<b>CERTIFICATES</b>	<b>Issued</b>	<b>Last Annual</b>	<b>Last Intermediate</b>	<b>Expires</b>
2.1	Safety Equipment Certificate (SEC):	01/10/2020	21/01/2022		24/10/2025
2.2	Safety Radio Certificate (SRC):	01/10/2020	23/09/2021		24/10/2025
2.3	Safety Construction Certificate (SCC):	01/10/2020	21/01/2022		24/10/2025
2.4	International Loadline Certificate (ILC):	01/10/2020	21/01/2022		24/10/2025
2.5	International Oil Pollution Prevention Certificate (IOPPC):	01/10/2020	16/11/2021		20/08/2022

2.6	International Ship Security Certificate (ISSC):	17/12/2020	N/A		04/11/2025
2.7	Maritime Labour Certificate (MLC):	17/12/2020	N/A		04/11/2025
2.8	ISM Safety Management Certificate (SMC):	17/12/2020	N/A		04/11/2025
2.9	Document of Compliance (DOC):	06/05/2020	N/A	11/12/2020	12/09/2023
2.10	USCG Certificate of Compliance (USCGCOC):	Not Applicable			Not Applicable
2.11	Civil Liability Convention (CLC) 1992 Certificate:	27/01/2022	N/A	N/A	04/02/2023
2.12	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	27/01/2022	N/A	N/A	04/02/2023
2.13	Liability for the Removal of Wrecks Certificate (WRC):	04/02/2022	N/A	N/A	04/02/2023
2.14	U.S. Certificate of Financial Responsibility (COFR):	Not Applicable	N/A	N/A	Not Applicable
2.15	Certificate of Class (COC):	12/07/2021	21/01/2022		24/10/2025
2.16	International Sewage Pollution Prevention Certificate (ISPPC):	01/10/2020	N/A	N/A	24/10/2025
2.17	Certificate of Fitness (COF):	Not Applicable			Not Applicable
2.18	International Energy Efficiency Certificate (IEEC):	08/05/2020	N/A	N/A	N/A
2.19	International Air Pollution Prevention Certificate (IAPPC):	14/01/2022 Re-issuance	21/01/2022	Not Applicable	24/10/2025

#### Documentation

2.20	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:				Yes
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?				Yes
2.22	Is the ITF Special Agreement on board (if applicable)?				N/A
2.23	ITF Blue Card expiry date (if applicable):				

<b>3.</b>	<b>CREW</b>				
3.1	Nationality of Master:				Greek
3.2	Number and nationality of Officers:	6			Greek
3.3	Number and nationality of Crew:	6			Greek
3.4	What is the common working language onboard:				Greek
3.5	Do officers speak and understand English?				Yes
3.6	If Officers/ratings employed by a manning agency - Full style:	N/A			N/A

<b>4.</b>	<b>FOR USA CALLS</b>				
4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter?				N/A
4.2	Qualified individual (QI) - Full style:		N/A		
4.3	Oil Spill Response Organization (OSRO) - Full style:		N/A		
4.4	Salvage and Marine Firefighting Services (SMFF) - Full Style:				

<b>5.</b>	<b>SAFETY/HELICOPTER</b>				
5.1	Is the vessel operated under a Quality Management System? If Yes, what type of system? (ISO9001 or IMO Resolution A.741(18) as amended):				Yes IMO Resolution A.741 (18)
5.2	Can the ship comply with the ICS Helicopter Guidelines?				No
5.2.1	If Yes, state whether winching or landing area provided:				
5.2.2	If Yes, what is the diameter of the circle provided:				

6. COATING/ANODES					
6.1	Tank Coating	Coated	Type	To What Extent	Anodes
	Cargo tanks:	Yes	Epoxy coating	Whole Tank	No
	Ballast tanks:	Yes	Whole Tank	Good	Yes
	Slop tanks:	Yes	Nippon Paint - Nippe Epoxy PC NOA	Whole Tank	No

7. BALLAST					
7.1	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Ballast Pumps:	1	Centrifugal	300 Cu. Metres/Hour	20 Metres
	Ballast Eductors:				

8. CARGO					
<b>Double Hull Vessels</b>					
8.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:			Yes, Solid	
<b>Cargo Tank Capacities</b>					
8.2	Number of cargo tanks and total cubic capacity (98%):			10	3,818.848 Cu. Metres
8.2.1	Capacity (98%) of each natural segregation with double valve (specify tanks):			Grp 1 - FO Cargo tank 1P – 301.526 Cargo tank 1S – 299.366 Cargo tank 4P – 413.268 Cargo tank 4S – 411.339  Grp 2- FO Cargo tank 2P – 408.185 Cargo tank 2S – 405.405 Cargo tank 5P – 377.923 Cargo tank 5S – 378.251  Grp 3- MGO Cargo tank 3P – 412.708 Cargo tank 3S – 410.875  Grand Total: 3.818,89  Grp 4- SLOP Cargo tank 6c – 115.962 (slop tank)	
8.2.2	IMO class (Oil/Chemical Ship Type 1, 2 or 3):			N/A	
8.3	Number of slop tanks and total cubic capacity (98%):			1	115.962 Cu. Metres
8.3.1	Specify segregations which slops tanks belong to and their capacity with double valve:			NO.4 group with 5S / 494.213m3 @ 98%	
8.3.2	Residual/retention oil tank(s) capacity (98%), if applicable:				
<b>SBT Vessels</b>					
8.3.3	What is total SBT capacity and percentage of SDWT vessel can maintain?				
8.3.4	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:			No	
<b>Cargo Handling and Pumping Systems</b>					
8.4	How many grades/products can vessel load/discharge with double valve segregation:			2	
8.4.1	State type of cargo containment (integral, independent, gravity or pressure tanks):			Integral	
8.5	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:			Yes 1.025 SG	
8.6	Max loading rate for homogenous cargo			With VECS	Without VECS
	Loaded per manifold connection:				600 Cu. Metres/Hour
	Loaded simultaneously through all manifolds:				1,500 Cu. Metres/Hour

<b>Cargo Control Room</b>				
8.7	Is ship fitted with a Cargo Control Room (CCR)?			Yes
8.8	Can tank innage/ullage be read from the CCR?			Yes
<b>Gauging and Sampling</b>				
8.9	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:	Yes, NA		
	What type of gauging system as per IBC 13.1 is fitted (Open/Restricted/Closed )?	Closed		
	What type of fixed closed tank gauging system is fitted:	Floating		
	Is a tank overflow control system fitted? If yes, then state if system includes automatic closing of valves?	No, N/A		
	Are high level alarms fitted to the cargo tanks? If Yes, indicate whether to all tanks or partial:	Yes, All		
8.9.1	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6?			Yes
8.9.2	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:	Yes, Digital Float Gauge / All cargo tanks		
8.10	Number of portable gauging units (example- MMC) on board:			2
<b>Vapor Emission Control System (VECS)</b>				
8.11	Is a vapour return system (VRS) fitted?	Yes		
8.12	Number/size of VECS manifolds (per side):	1		150 Millimetres
8.13	Number/size/type of VECS reducers:	NA		
<b>Venting</b>				
8.14	State what type of venting system is fitted:	Independent high velocity P/V valves		
<b>Cargo Manifolds and Reducers</b>				
8.15	Total number/size of cargo manifold connections on each side:	4/300 Millimetres (300, 300, 200, 200 Millimetres)		
8.15.1	Does the vessel have a Common Line Manifold connection? If yes, describe:	No		
8.16	What type of valves are fitted at manifold:	Gate		
8.17	What is the material/rating of the manifold:	Stainless steel SUS 304/SS SUS304 10kg/cm2/SS SUS304		
8.17.1	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?	Yes		
8.18	Distance between cargo manifold centers:	1,500 Millimetres		
8.19	Distance ships rail to manifold:	2,410 Millimetres		
8.20	Distance manifold to ships side:	2,600 Millimetres		
8.21	Top of rail to center of manifold:	1,500 Millimetres		
8.22	Distance main deck to center of manifold:	2,600 Millimetres		
8.23	Spill tank grating to center of manifold:	749 Millimetres		
8.24	Manifold height above the waterline in normal ballast/at SDWT condition:	4.81 Metres		3.41 Metres
8.25	Number/size/type of reducers:	2 x 300/250mm (12/10") 2 x 250/200mm (10/8") 2 x 200/150mm (8/6") 2 x 200/100mm (8/4") 2 x 150/100mm (6/4") ASA		
8.26	Is vessel fitted with a stern manifold? If yes, state size:	Yes (1 no. /200MM, 1 no. /300MM), 300 Millimetres		
<b>Heating</b>				
8.27	Cargo/slop tanks fitted with a cargo heating system?	Type	Coiled	Material
	Cargo Tanks:	Thermal Oil Heating	Yes	SS
	Slop Tanks:	Thermal Oil Heating	Yes	SS SUS304 Sch 20
8.27.1	Is a Thermal Oil Heating system fitted? If yes, identify tanks?	Yes, All tanks		
8.28	Maximum temperature cargo can be loaded/maintained:		60.0 °C / 140.0 °F	60 °C / 140 °F

8.28.1	Minimum temperature cargo can be loaded/maintained:	60.0 °C / 140.0 °F	60.0 °C / 140.0 °F
<b>Inert Gas and Crude Oil Washing</b>			
8.29	Is an Inert Gas System (IGS) fitted/operational?	No/	
8.29.1	Is a Crude Oil Washing (COW) installation fitted/operational?	No/	
8.30	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:		
8.30.1	If nitrogen generator, specify the applicable flow rate for each of the designed purity modes:	NA	
<b>Cargo Pumps</b>			
8.31	How many cargo pumps can be run simultaneously at full capacity:	1	
8.32	Pumps	No.	Type
	Cargo Pumps:	2	Screw
		1	Screw
		1	Screw (slop pump)
	Cargo Eductors:		
	Stripping:		
8.33	Is at least one emergency portable cargo pump provided?	N/A	
<b>Tank Cleaning Systems</b>			
8.34	Is tank cleaning equipment fixed in cargo tanks?	No	
8.35	Is portable tank cleaning equipment provided?	Yes	
8.36	Tank washing pump capacity:	20 Cu. Metres/Hour	
8.37	Is a washing water heater fitted? If yes is it operational and state max washing water temperature:	Yes, Yes 80 Degrees Celsius	
8.38	What is the maximum number of machines that can be operated at their designed max pressure?	2	
<b>Other Deck Equipment</b>			
8.39	Is vessel fitted with a remote cargo tank temperature monitoring system. If yes, is it operational?	Yes, Yes	
8.40	Is vessel fitted with a remote cargo tank pressure monitoring system. If yes, is it operational?	Yes, Yes	
8.41	Is vessel fitted with a cargo tank drier. If yes is it operational and state capacity:	No, N/A	
8.42	Is vessel fitted with a cargo cooling system. If yes is it operational and state tanks applicable:	No, N/A NA	
8.43	Is steam available on deck?	Yes	

<b>9.</b>	<b>MOORING</b>					
9.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
9.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:					
	Main deck fwd:					
	Main deck aft:					
	Poop deck:					
9.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	45.00 Millimetres	Polyester mixed	200.00 Metres	31.00 Metric Tonnes
	Main deck fwd:					
	Main deck aft:					
	Poop deck:	4	45.00	Polyester mixed	200.00 Metres	31.00 Metric Tonnes

			Millimetres			
9.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	2	45.00 Millimetres	Polyester mixed	200.00 Metres	31.00 Metric Tonnes
	Main deck fwd:	2	45.00 Millimetres	Polypropelene / Polyester mixed	220.00 Metres	31.00 Metric Tonnes
	Main deck aft:	1	45.00 Millimetres	8 Strands Polypropylene & Polyester Composite	200 Metres	31 Metric Tonnes
	Poop deck:	1	45 Millimetres	Polyester mixed	200 Metres	30 Metric Tonnes
9.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	4	Double Drums	Hydraulic	18.00 Metric Tonnes	
	Main deck fwd:					
	Main deck aft:					
	Poop deck:	4	Double Drums	Hydraulic	18.00 Metric Tonnes	
9.6	Bitts, closed chocks/fairleads	No. Bitts	SWL Bitts	No. Closed Chocks	SWL Closed Chocks	
	Forecastle:	4	28 Metric Tonnes	3	63 Metric Tonnes	
	Main deck fwd:	2	28 Metric Tonnes	2	13 Metric Tonnes	
	Main deck aft:	2	12 Metric Tonnes	2	13 Metric Tonnes	
	Poop deck:	4	28 Metric Tonnes	3	63 Metric Tonnes	

#### Anchors/Emergency Towing System

9.7	Number of shackles on port/starboard cable:				9/9	
9.8	Type/SWL of Emergency Towing system forward:				NA	
9.9	Type/SWL of Emergency Towing system aft:				NA	
9.10.1	What is size of closed chock and/or fairleads of enclosed type on stern					200 x 300

#### Escort Tug

9.10.2	What is SWL of closed chock and/or fairleads of enclosed type on stern:					64 Metric Tonnes
9.11	What is SWL of bollard on poop deck suitable for escort tug:					28 Metric Tonnes

#### Lifting Equipment/Gangway

9.12	Derrick/Crane description (Number, SWL and location):					Cranes: 1 x 2.5 Tonnes 1 x 5 T - Manifold Area (Hose Handling Crane) 1 x 2.5 T- Stern, starboard side
9.13	Accommodation ladder direction:					
	Does vessel have a portable gangway? If yes, state length:					Yes, 6 Metres

#### Single Point Mooring (SPM) Equipment

9.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)':?					No
9.15	If fitted, how many chain stoppers:					
9.16	State type/SWL of chain stopper(s):				Not fitted	
9.17	What is the maximum size chain diameter the bow stopper(s) can handle:					
9.18	Distance between the bow fairlead and chain stopper/bracket:					0 Metres
9.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:				No size 360 x260mm	

#### 10. PROPULSION

10.1	Speed		Maximum	Economical		
	Ballast speed:		12.50 Knots (WSNP)	11 Knots (WSNP)		
	Laden speed:		11.50 Knots (WSNP)	10.50 Knots (WSNP)		
10.2	What type of fuel is used for main propulsion/generating plant:		Diesel	Diesel		
10.3	Type/Capacity of bunker tanks:		Fuel Oil: 0 Cu. Metres			

		Diesel Oil: 261.92 Cu. Metres Gas Oil: 0 Cu. Metres		
10.4	Is vessel fitted with fixed or controllable pitch propeller(s):	Fixed		
10.5	Engines	No	Capacity	Make/Type
	Main engine:	1	1,618 Kilowatt	LH34LA Hanshin Diesel
	Aux engine:	3	265 Kilowatt	Yanmar co. ltd / 6HAL2-HTN
	Power packs:			
	Boilers:	1	2,320 Metric Tonnes/Hour	Miura / HTB -200L
<b>Bow/Stern Thruster</b>				
10.6	What is brake horse power of bow thruster (if fitted):	Yes, 320.00 bhp		
10.7	What is brake horse power of stern thruster (if fitted):	N/A, 0 bhp		
<b>Emissions</b>				
10.8	Main engine IMO NOx emission standard:	Tier I		
10.9	Energy Efficiency Design Index (EEDI) rating number:	N/A		

<b>11.</b>	<b>SHIP TO SHIP TRANSFER</b>		
11.1	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquified Gas, as applicable)?	No	
11.2	What is maximum outreach of cranes/derricks outboard of the ship's side:	3.00 Metres	
11.3	Date/place of last STS operation:	NA	

<b>12.</b>	<b>RECENT OPERATIONAL HISTORY</b>		
12.1	Last three cargoes/charterers/voyages (Last/2nd Last/3rd Last):	MGO/ VLSFO	
12.2	Has vessel been involved in a pollution, grounding, serious casualty, unscheduled repair or collision incident during the past 12 months? If yes, provide details:	Pollution: No, Grounding: No, Casualty: No, Repair: No, Collision: No,	
12.3	Date and place of last Port State Control inspection:	13/03/2020 / Agioi Theodoroi / ParisMou 07/10/2020 Elefsis & Piraeus pthap	
12.4	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No	
12.5	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: <i>* "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.</i>	More info owners	
12.6	Date/Place of last SIRE inspection:	N/A	
12.6.1	Date/Place of last CDI inspection:	N/A	
12.7	Additional information relating to features of the ship or operational characteristics:	Nil	

Revised 2018 ([INTERTANKO/Q88.com](http://www.intertanko.com))

Form completed on <http://www.q88.com/integration.aspx> Please email [support@q88.com](mailto:support@q88.com) an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee